



Malarkey® Roofing System Coordinated Roofing Components

Performance Underlayments

Offering polymer modified and synthetic underlayments, ice and water protection, and more.



SECURE START™

Starter Shingles

Smart Start™ shingles separate at a perforation to provide two, full-size starter shingles with seal-down.

SMART START™

Hip and Ridge Shingles

Choose from high-profile EZ-Ridge™ or traditional low-profile RidgeFlex™ hip and ridge shingles.

RIDGEFLEX™ EZ-RIDGE™

**SECURE
CHOICE™
= SYSTEM =**

The Secure Choice™ roofing system by Malarkey Roofing Products® is a family of residential products to support our many shingle lines. Beginning at the roof deck, the system includes underlayments, as well as starter shingles, field shingles, and hip and ridge shingles. These products are manufactured and controlled for quality and dependability. **Together, the components of a Malarkey Roofing System assure homeowners that their choice is a Secure Choice™.**

EZ-RIDGE™

HIP AND RIDGE SHINGLE

SECURE START®

UNDERLAYMENT LINE

WINDSOR®
STARTER SHINGLE

STARTER SHINGLE



Residential Supporting Products

For added system protection, Malarkey supports the roofing system with a variety of performance-driven underlayments:

Right Start™ UDL

A durable fiberglass underlayment barrier for your roof deck, Right Start™ UDL, manufactured with NEX® polymer modified asphalt technology, provides tear resistance and watertight protection. Performing in all weather conditions for over 25 years, our UDL is the right start to any steep slope system.

Approx. Wt./Roll: 80 lbs. [36.3 kg]
Coverage: 2 squares
Width: 39³/₈" [1 m]
Length: 66' [20.1 m]

- Water-Resistant Underlayment
- Perfect Underlayment and Dry-in Sheet for Steep Slope Roofing Applications
- ASTM D4601 Type II; ASTM D4869; ASTM D226 Type II; ASTM D6757 Type II; ICC Approval - ESR-1561; FBC Approvals - #14807 & #15214
- NEX® Polymer Modified Asphalt
- Thickness: 55 mils [nominal]
- ASTM E108 Class A Fire Rating

401 Arctic Seal®

Our NEX® polymer modified self-adhering underlayment provides added protection against leaks to your roof deck caused by ice damming. Arctic Seal® is also useful as a flashing membrane in areas susceptible to leaks such as valleys and roof-to-sidewall transitions.

Approx. Wt./Roll: 60 lbs. [27.2 kg]
Coverage: 2 squares [approx.]
Width: 36" [0.91 m]
Length: 65' [19.8 m]

- Self-Adhering, Waterproof Underlayment
- Ideal for Low Slope Application, 2:12 up to 4:12
- Guards Against Ice Damming and Wind-Driven Rain
- Thickness: 55 mils [nominal]
- NEX® Polymer Modified Asphalt
- Split-Release Film for Easy Application
- Protects Valleys, Roof Perimeters, and Penetrations
- ASTM D1970

406 Secure Start® HT

Secure Start® HT is a self-adhering, high-temperature underlayment primarily intended for complete deck coverage under metal but also recommended for high elevations, climates causing ice dams, and areas with high winds or wind-driven rain.

Approx. Wt./Roll: 40 lbs. [18.1 kg]
Roll Size: 2 squares
Width: 36" [0.91 m]
Length: 67' [20.4 m]

- Self-Adhering, High-temperature, Waterproof Underlayment; Ideal Under Metal Roofs
- Thermal Stability to 260°F [127°C]
- ASTM E108 Class A Fire Rating
- Seals Around Nails
- 6 Months UV Exposure
- Anti-Skid, Walkable Surface
- ASTM D1970

1030 Secure Start® SG

Malarkey's Secure Start® SG is a lightweight, smooth grade synthetic underlayment suitable for use in steep slope roofing applications with asphalt shingles, wood shakes/shingles, roof tile, and metal. Its smooth surfaces, top and bottom, lessen shingle drag and speed installation.

Approx. Wt./Roll: 25 lbs. [11.3 kg]
Roll Size: 10 squares
Width: 48" [1.2 m]
Length: 250' [76.2 m]

- Lightweight, Smooth-grade Synthetic Underlayment and Dry-in Sheet for Steep Slope Roofing Applications
- Smooth Grade/Quick-lay Application
- ICC-ES AC188; ASTM D226; ASTM D4869; CCRR-1082; CAN/CSA A123.3; FBC FL23186
- 6 Months UV Exposure
- Lays Flat, Straight, and Wrinkle Free
- 100% Recyclable
- ASTM E108 Class A Fire Rating

1031 Secure Start® Plus

Malarkey's Secure Start® Plus is a lightweight, synthetic underlayment engineered to perform in all weather conditions -40°F to 240°F [-40°C to 116°C]. Anti-skid technology securely holds the underlayment in place and provides a walkable surface, assuring steep slope projects get done quickly and safely.

Approx. Wt./Roll: 30 lbs. [13.6 kg]
Roll Size: 10 squares
Width: 48" [1.2 m]
Length: 250' [76.2 m]

- Lightweight, Synthetic Underlayment and Dry-in Sheet for Steep Slope Roofing Applications
- Lays Flat, Straight, and Wrinkle Free
- ICC-ES AC188; ASTM D226; ASTM D4869; CCRR-1082; CAN/CSA A123.3; FBC FL23186
- 6 Months UV Exposure
- Anti-Skid Surfaces, Top and Bottom
- 100% Recyclable
- ASTM E108 Class A Fire Rating

1035 Secure Start® Permeable

Malarkey's Secure Start® Permeable is a breathable, synthetic underlayment engineered to both prevent water from penetrating a roof plus help release trapped moisture from poor attic ventilation. Lightweight despite three durable layers, the middle is a monolithic membrane providing vapor permeability.

Approx. Wt./Roll: 20 lbs. [9 kg]
Roll Size: 5 squares
Width: 48" [1.2 m]
Length: 125' [38.1 m]

- Lightweight, Synthetic Underlayment and Dry-in Sheet for Steep Slope Roofing Applications
- Lays Flat, Straight, and Wrinkle Free
- ICC-ES AC188; ASTM D226 Type I and II; ASTM D4869; CCRR-1082; CAN/CSA A123.3; FBC FL23186
- Breathable Membrane Releases Trapped Moisture
- 6 Months UV Exposure
- Anti-Skid Surfaces, Top and Bottom
- 100% Recyclable
- ASTM E108 Class A Fire Rating

A properly designed roof involves a coordinated system of products. Malarkey offers a family of roofing products that ensure **quality, protection, and security.**

SMART START™

Malarkey's Smart Start™ code-compliant starter shingles are made with sustainable NEX® polymer modified asphalt technology and manufactured with exceptional sealant for increased wind protection at eave and rake edges. Holding fast the leading edge of the first course of field shingles, the dimensions of Smart Start™ starter shingles extend up beyond the fastening point of the shingles, providing maximum protection against wind uplift and moisture migration.



WINDSOR® STARTER SHINGLE

Windsor® Starter is color blended to match the Windsor® shingle line, features Scotchgard™ Protector from 3M, and made with NEX® polymer modified asphalt.

RIDGEFLEX™, EZ-RIDGE™ + EZ-RIDGE XT™

Malarkey offers two different profiles: high-profile EZ-Ridge™ as well as traditional low-profile RidgeFlex™. All hip and ridge products from Malarkey feature Scotchgard™ Protector from 3M, NEX® polymer modified asphalt, and a high-performance UL 2218 Class 4 impact resistance rating.



Complementary components to the Secure Choice™ System:

OMNISEAL™ + PARAGON® CHROMA CAP

Malarkey provides low slope, colored cap sheets to complement our residential shingle system. OmniSeal™ cap sheets and Paragon® CHROMA Cap are ideal for any low slope residential project.

